

PENN YAN AERO SERVICE, INC.

2499 BATH ROAD VIGLOBI PENN YAN, NY 14527 9599

180 H.P. SUPERHAWK

(315) 536-2333

The Engine People

FAA APPROVED

SUPPLEMENTAL AIRPLANE FLIGHT MANUAL

FOR

CESSNA 172N

REG. NO. N737168

SER. NO. 172676627

This Supplement must be carried in the aircraft when it is modified by the installation of a 180 HP engine and the gross weight is increased in accordance with STC SA703GL. The information contained herein supplements or supersedes the basic placards and markings only in those areas listed.

FAA APPROVED: 0

FOR W. F Horn, Manager Chicago Aircraft

Certification Office

FAA Central Region

DATE: - June 11, 1985

PENN YAN AERO SERVICE INC.

FAA APPROVED
SUPPLEMENTAL AIRPLANE FLIGHT MANUAL
FOR
CESSNA 172 SERIES AIRCRAFT

LOG OF REVISIONS

Rev.	Page	Description	FAA Approved	Date
<u>No</u> . A	<u>No</u> . 4	Added performance information to section 5 for clarification		
		Renumbered pages	Irwin N Brumer Manager, NYACO	APR 1 3 1994

Penn Yan Aero Service, Inc. 2499 Bath Road, Airport Penn Yan, NY 14527-9599 Supplemental Airplane Flight Manual for Cessna 172N

SECTION I - Limitations

A. The following placard must be displayed in full view of the pilot:

THIS AIRCRAFT HAS BEEN MODIFIED BY THE INSTALLATION OF A 180 HP ENGINE PER STC SA703GL. IT MUST BE OPERATED AS A NORMAL CATEGORY AIRPLANE IN COMPLIANCE WITH THE OPERATING LIMITATIONS AS STATED IN THE FORM OF PLACARDS, MARKINGS AND MANUALS.

B. For the N model aircraft the following placard must be displayed adjacent to the flap position selector switch:

MAXIMUM FLAP TRAVEL IS 30°

C. The following limits apply to the normal category only.

Maximum Gross Weight - 2550 lbs.

C.G. Range - 41.0" to 47.3" at 2550 lbs.

35.0" to 47.3" at 1950 lbs. or less

Straight line variation between points given.

MAX WEIGHT 2550

Section 3 Emergency Procedures

NO CHANGE

Section 4 Normal Procedures

NO CHANGE

Section 5 Performance

Performance of the Cessna 172 series aircraft, when it is modified by the installation of a 180 HP engine and the gross weight is increased, in accordance with STC SA703GL, will be equal to or better than the basic airplane

CAUTION: -

The fuel consumption and range/endurance information originally presented for this model do not apply to this STC modification; increased fuel consumption and reduced range/endurance can be expected with the 180 hp engine installed.

FAA APPROVED DATE:

Revised: APR 13 1994

÷	6									CUI	RVE	NO.	335
2		AVI	L F	YCOI	MINO	3	CENT 0-36	T RA 50, 18	30 HP	SER	VER IES		
		S.	OMPRE PARK	SS101 NDV	N RAT	Γ10			8 25°	50:1 BTC		-	
						. 7							
				Ь									
,	-16-												
S. GAL./HR.		a.									-		
	-14												
	-12-								£ 1, £ 1,0	72			
1- U.S.								WABLE					
FUEL FLOW-U.	-10-						RY	<i>y</i>					
					W)	MINIT	7						
	8				· ·				=				
	-6-		<i></i>		×								
								7					
		5	o O	6 9	0	70 CENT	0	80	O OWER	90) , .	10	0